

What is claimed is:

1. A probe head for a coordinate measuring apparatus, the probe head comprising:

a yielding part;

measuring systems for measuring the deflection of said
5 yielding part in respective directions;

a damping device for damping said yielding part in a
pregiven direction; and,

said damping device including at least one friction brake
for generating a friction force which can be electrically
10 changed.

2. The probe head of claim 1, said friction brake including a
flag and an electromagnet for electromagnetically drawing said
flag to said electromagnet.

3. The probe head of claim 2, wherein said flag is a first flag
and said damping device includes a second flag; and, said first
and second flags coact electromagnetically with said
electromagnet.

4. The probe head of claim 3, wherein at least one of said first
and second flags is reinforced in the region of said
electromagnet.

5. The probe head of claim 1, said damping device further
comprising clamping means for clamping said flag.

6. The probe head of claim 5, wherein said flag has a side

facing away from said electromagnet; and, said clamping means comprises a plate disposed on said side of said flag in spaced relationship thereto; a holder; and, said plate is resiliently mounted on said holder so as to permit a displacement relative thereto when said plate is drawn by said electromagnet to clamp said flag therebetween.

7. The probe head of claim 6, wherein said plate has a thickness greater than the thickness of said flag.

8. The probe head of claim 1, further comprising an electronic controller for electrically adjusting said friction force of said friction brake.

9. The probe head of claim 8, said electronic controller including means for adjusting said friction force in proportion to the time-dependent derivative of the measured deflection in a particular direction (x, y, z).

10. The probe head of claim 9, said electronic controller including means for clamping said probe head for a short time to counter a rebound of the probe head during a contacting operation.

11. The probe head of claim 8, said friction brake including a flag and an electromagnet coacting with said flag; and, said electronic controller including means for applying an alternating current to said electromagnet for generating a low damping.

12. The probe head of claim 8, said friction brake including a

flag; an electromagnet coacting with said flag; and, a
spring-suspended plate in spaced relationship to said flag; said
electronic controller including means for clamping said friction
5 brake by first applying a voltage (U_{sp}) above a threshold
plate (U_{plate}) so that said spring-suspended plate is pulled toward
said electromagnet and then dropping said voltage (U_{sp}) to below
said threshold voltage (U_{plate}) after said spring-suspended plate
has been pulled toward said electromagnet.

13. The probe head of claim 8, further comprising a measuring
force generator drivable by said electronic controller; and, for
clamping said yielding part in a pregiven desired position of a
corresponding one of said measuring systems, said electronic
5 controller functioning to clamp said friction brake in a desired
position of said yielding part; and, causing said measuring force
generator to generate pulse-like measurement forces opposite to
the direction of the deflection relative to said desired position
until said corresponding one of said measuring systems is in its
10 zero position.

14. The probe head of claim 8, wherein said electronic
controller increases the friction force of said friction brake or
clamps said friction brake during acceleration operations of said
probe head.